Western Agricultural Lime Co (Australia) Manypeaks

WALCO

LIME SUPPLIES

Free Call 1800 803 003

PO Box 40 PEMBERTON WA 6260

walco@westnet.com.au





Approved Laboratory



Walco	Date of Analysis	February 27th 2012
Manypeaks	Laboratory No.	11A0422-007
Chalk Lime	Product Screened	Yes
Compuload Loader Scales	Screen Size (mm)	N/A
/	Manypeaks Chalk Lime	Manypeaks Laboratory No. Chalk Lime Product Screened

CODE OF PRACTICE APPROVED LABORATORY REPORT					
	THIS SAMPLE	RANGE FOR PIT	THIS SAMPLE	RANGE FOR PIT	
Sieve Range (mm)	% Weight		% Neutralising Value		
0.000 - 0.125	7.7	7.0 - 9.7	78.0	77.0 - 85.3	
0.125 - 0.250	13.0	4.9 - 15.0	73.2	73.2 - 79.4	
0.250 - 0.500	15.3	11.2 - 17.3	78.2	78.2 - 80.4	
0.500 – 1.000	8.7	8.7 - 17.7	76.9	76.9 - 78.2	
> 1.000	55.3	41.8 - 59.1	72.5	72.5 - 74.3	
Weighted Average NV			74.3	74.3 - 77.8	
Bulk NV	74.1	74.1 - 76.4	Department of Agriculture and Food Product sampled by the Department of Agriculture and Food, and submitted directly to the Chem Centre for testing as part of the Lime WA Inc. independent audit program.		
Calcium (Ca) (1 M HCI)	28.7	28.7 - 31.2			
Magnesium (Mg) (1 M HCI)	0.6	0.4 - 0.6			
Sodium (Na) (1 M HCI)	0.1	0.1			

Statement by Supplier: The above analysis, provided by a Code of Practice approved laboratory, is a true representation of the product being supplied from the nominated pit. Pit ranges have been calculated from the last 3 samples analysed.				
Date :	Name :	Signature :		

Disclaimer: Lime WA Inc. requires members to provide the above details in accordance with the industry Code of Practice requirements but makes no claims and provides no guarantees on the quality or suitability of the product supplied. Product supplied by Lime WA Inc. members occurs naturally and has a moisture retention capacity that varies according to seasonal conditions. As this cannot be controlled by suppliers, moisture level analyses are not included on this information sheet. Lime WA Inc. is not responsible for any claims and/or liabilities arising from the supply and/or use of the product supplied. However, users are invited to contact the Association on 0419 575 737 in the event of any dissatisfaction with the product description provided by accredited lime suppliers.